

TransferRite®

RV, Fleet and Marine Products

High performance products for demanding applications

Ultra adhesive formula

- Provides adhesion to exposed liner
- Reduces tunneling and dog-eared corners
- Available on paper and film products
- Ideal for graphics that are rolled and shipped

Heavyweight paper premask

- Resist temperature and humidity fluctuations
- Dimensional stability
- Strength to withstand applications over rivets and corrugations, and on compound curves
- Won't tear when you least expect it
- Products for textured and hard to lift films
- Gentle on digital prints

Lightweight paper premask

- Low tack option for easy removal
- Economical choice for RV paint mask installation

AirMask®

AirMask® film premask

- Excellent adhesion to all brands of exposed air egress liners
- Eliminates the need for heat vacuum
- Recommended for partial wraps
- Removes from vinyl "like butter"



Lightweight papers are commonly used for the installation of RV spray.



AirMask® film premask is the leading solution for adhesion to exposed air egress liners.



TransferRite®

Product Selection Guide: RV, Fleet and Marine

PRODUCT NUMBER	TACK LEVEL	THICKNESS PSTC-33 (mils)	ELONGATION PSTC-31 (%)	PRODUCT HIGHLIGHTS AND RECOMMENDED USES
560U	Low	4	2%	RV paint mask installation
760U	Low	5	6%	Large, one-piece decals; RV paint mask installation; Unprinted vinyl parts; Digital prints
782U	Medium	5	6%	Graphics requiring long-term storage; 3M cross reference SCPM3
792U	High	5	6%	Fine plotter and die cut graphics; 3M cross reference SCPS2
6882	Medium	6	6%	Decals printed with UV inks; Digital prints
AirMask	Medium	4	570%	Film premask that adheres to exposed air-egress liners
992U	High	7	6%	Paper premask that adheres to exposed air egress liners

Applications recommendations - the performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American Biltrite Inc. assumes no liability for claims beyond the replacement value of any defective products, and is in no way liable for consequential or incidental damages. These products (unless otherwise noted) are not suitable for prolonged outdoor exposure.



105 Whittendale Drive • Moorestown, NJ 08057
 PH: (856) 778-0708 • FAX: (856) 778-7485
 Toll Free Fax: 888-224-6325 (US Only)

WWW.ABITAPE.COM