



AutoWrap® 0895

PRODUCT DESIGN

AutoWrap 0895 is a clear, pressure sensitive, adhesive coated polyolefin film masking. The product is UV stabilized and designed to protect automotive finishes during transit to the dealer and for storage.

APPLICATION

AutoWrap 0895 protects automotive paint systems during shipment to dealer and in storage. 0895 is also used for automotive components shipped to assembly plants.

PERFORMANCE FEATURES

- Easy, one-piece removal leaves surfaces clean and stain-free
- Easily removable, even after extended periods of time
- Stays intact over bends and curved surfaces
- Adheres evenly to the applied surface
- Resists edge lift during transportation

PHYSICAL PROPERTIES	VALUE
Colors	Clear
Nominal Thickness	2 mils (0.05 mm)
Adhesion (@90°)	11 oz/in (3.0 N/25 mm)
Tensile Strength	17 lb/in (74 N/25 mm)
Elongation %	665
Backing	Polyolefin
Printable Surface	No

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-060321



ABI Tape

105 Whittendale Drive, Moorestown, NJ 08057
Toll Free: 856-778-0708 • WWW.ABITAPE.COM