



ProtectRite® 6760

PRODUCT DESIGN

ProtectRite 6760 is a heavy duty, printable rubber fibrous paper backing with a specially formulated latex pressure sensitive adhesive system.

APPLICATION

ProtectRite 6760 is designed to protect highly polished surfaces such as polished stainless steel, painted steel, chrome plated steel, and polished brass with a medium tack adhesive for easy removal. 6760 is also used on mill finished and painted aluminum, specialty metals, synthetic marble, glass, and high pressure laminates requiring a high finish.. It can be used to protect aluminum aircraft skin during forming and processing.

PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- One piece removal leaves surfaces clean and stain-free
- Universal adhesive offers application over a broad range of surfaces

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	5 mils (0.13 mm)
Adhesion (@90°)	7 oz/in (1.9 N/25 mm)
Tensile Strength	21 lb/in (92 N/25 mm)
Elongation	14%
Backing	Paper
Printable Surface	Yes

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-070721