



# ProtectRite® 7305

## PRODUCT DESIGN

ProtectRite 7305 is a 3 mil low density polyolefin film with a formulated acrylic pressure sensitive adhesive.

## APPLICATION

ProtectRite 7305 is generally used to protect smooth and matte polycarbonate, medium polish stainless steel, anodized aluminum, painted metals, and mill finish aluminum.

## PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- Conformable even during extreme bending
- Can be supplied imprinted with your logo, signature, or application instructions
- The controlled unwind allows for easy application using either manual or automatic methods

PHYSICAL PROPERTIES	VALUE
Colors	Clear, White, Blue
Nominal Thickness	3 mils (0.08 mm)
Adhesion (@180°)	7.5 oz/in (2.1 N/25 mm)
Tensile Strength	7.5 lb/in (33 N/25 mm)
Elongation	325%
Backing	LDPE
Printable Surface	No

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-072121