



## ProtectRite® 8502

### PRODUCT DESIGN

ProtectRite 8502 is a 2 mil smooth polypropylene film masking with a solvent rubber adhesive system. 8502 is designed for applications where die-cutting is typically utilized.

### APPLICATION

ProtectRite 8502 is suggested for use on partially cured paints and coatings, lacquer-coated aluminum, die-cutting applications, and sublimation of trophy stock metal. 8502 is also used to protect appliance metals.

### PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- One piece removal leaves surfaces clean and stain-free
- Specially designed adhesive system resists build, making for a uniform adhesion

| PHYSICAL PROPERTIES | VALUE                  |
|---------------------|------------------------|
| Colors              | Clear, Green           |
| Nominal Thickness   | 2 mils (0.05 mm)       |
| Adhesion (@90°)     | 11 oz/in (3.0 N/25 mm) |
| Tensile Strength    | 15 lb/in (66 N/25 mm)  |
| Elongation          | 600%                   |
| Backing             | Smooth Polypropylene   |
| Printable Surface   | No                     |

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-072121

**ProtectRite®**

**ABI Tape**

105 Whittendale Drive, Moorestown, NJ 08057  
Toll Free: 856-778-0708 • [WWW.ABITAPE.COM](http://WWW.ABITAPE.COM)