



ProtectRite® 8510

PRODUCT DESIGN

ProtectRite 8510 is a 3 mil low UV stable CoEx polyolefin film with a solvent rubber adhesive. 8510's adhesive system offers uniform adhesion over a variety of surfaces and can be applied over partially cured paints and coatings.

APPLICATION

ProtectRite 8510 is used to protect metals and coated metal surfaces during fabrication outdoors for no more than six months.

PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- One piece removal leaves surfaces clean and stain-free
- Specially designed adhesive system resists build, making for a uniform adhesion

PHYSICAL PROPERTIES	VALUE
Colors	Clear, White, Blue
Nominal Thickness	3 mils (0.08 mm)
Adhesion (@90°)	11 oz/in (3.0 N/25 mm)
Tensile Strength	11 lb/in (48 N/25 mm)
Elongation	450%
Backing	CoEx
Printable Surface	No
Shelf Life	24 Months

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company - BSI Certificate #FM 26197. MK-072121