

TransferRite Ultra® 992U

PRODUCT DESIGN

TransferRite Ultra 992U is a heavyweight saturated with a unique rubber-based adhesive system that provides superior adhesion to exposed textured liners.

APPLICATION

TransferRite Ultra 992U is used with large format, repositionable graphics, die-cuts on textured liners, and digitally and screen-printed graphics.

PERFORMANCE FEATURES

- Exceptional dimensional stability
- Ultra adhesion to exposed textured liners, ensuring smooth lamination
- Trouble-free storage, shipping, and installation

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	7 mils (0.18 mm)
Adhesion (@90°)	9.5 oz/in (2.6 N/25 mm)
Tensile Strength	20 lb/in (88 N/25 mm)
Elongation	14%

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Biltrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Biltrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-071421



Toll Free: 856-778-0708 • WWW.ABITAPE.COM