



# Ideal Tape® 9145, Polyester Film

## PRODUCT DESIGN

Ideal Tape 9145 is a 1 mil polyester film with a low tack pressure sensitive rubber adhesive system.

## APPLICATION

Ideal Tape 9145 is designed to protect circuit boards from contamination and chemical damage.

## PERFORMANCE FEATURES

- Polyester film backing will not break or tear upon removal and protects against abrasion from rough surfaces, fumes, and chemicals
- Conformable backing suitable for either hand or automatic application
- Low tack adhesive provides an easy, low residue removal and resists degradation from chemicals and fumes

PHYSICAL PROPERTIES	VALUE
Color	Orange
Backing Thickness	1 mil (0.03 mm)
Total Thickness	2 mils (0.06 mm)
Adhesion to Steel	10 oz/in (2.7 N/25 mm)
Tensile Strength	23 lb/in (101 N/25 mm)
Elongation	100%
Backing	Polyester Film
Adhesive System	Rubber

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. Ideal Tape Co., assumes no liability for claims beyond the replacement value of our product proved to be defective. Note: Tape should be stored in its original packaging in a cool, dry area (60°F to 80°F and 50% relative humidity) away from direct sunlight. Tape should be used within 12 months from the date of shipment. Application surfaces should be clean, dry and free of grease, oil or other contaminants. MK-081021

**Ideal Tape Co., Inc.**

1400 Middlesex Street, Lowell, MA 01851

Toll Free: 800-229-9148 • [WWW.IDEALTAPE.COM](http://WWW.IDEALTAPE.COM)