



ProtectRite® 6582

PRODUCT DESIGN

ProtectRite 6582 is a custom designed moisture resistant saturated fibrous paper backing coated with a specially made rubber based pressure sensitive adhesive system. 6582 protects surfaces from abrasion during processing, fabricating, and shipping.

APPLICATION

ProtectRite 6582 is used on acrylic and polycarbonate sheet, stainless steel, and aluminum and high pressure laminates.

PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- One piece removal leaves surfaces clean and stain-free
- Universal adhesive offers application over a broad range of surfaces

PHYSICAL PROPERTIES	VALUE
Colors	White
Nominal Thickness	4 mils (0.10 mm)
Adhesion (@90°)	7 oz/in (1.9 N/25 mm)
Tensile Strength	20 lb/in (88 N/25 mm)
Elongation	3%
Backing	Paper
Printable Surface	Yes

CLASSIFICATIONS

Boeing Approved; BAC-5034

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company - BSI Certificate #FM 26197. MK-080921