



# ProtectRite® 6926

## PRODUCT DESIGN

ProtectRite 6926 is a high grade, heavy duty, abrasion resistant paper backing coated with specially formulated latex pressure sensitive adhesive system.

## APPLICATION

ProtectRite 6926 can be used on stainless steel, aluminum, painted metals, acrylic, and polycarbonate.

## PERFORMANCE FEATURES

- Easily removable, even over extended time periods
- One piece removal leaves surfaces clean and stain-free
- Conformable in both machine and cross web direction
- Resists lifting during excessive bending

PHYSICAL PROPERTIES	VALUE
Colors	Tan
Nominal Thickness	11 mils (0.28 mm)
Adhesion (@90°)	9 oz/in (2.5 N/25 mm)
Tensile Strength	39 lb/in (171 N/25 mm)
Elongation	10%
Backing	Paper
Printable Surface	No

All product properties are measured in accordance with Pressure Sensitive Tape Council and/or ASTM test methods. The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for his intended use. American Bilrite assumes no liability for claims beyond the replacement value of our product proved to be defective. American Bilrite Inc. Tape Products Division is an ISO 9001 Certified company – BSI Certificate #FM 26197. MK-080921